



**High Quality Woodcare Products**  
**Industrial Finishes**



# Color Fixing Primers

## WOODLOOK / ECOFIX / OCULTO

### PRODUCT DESCRIPTION

ECOFIX, ECOFIX WOODLOOK and OCULTO are water based impregnation oils for parquet and wooden furniture. The wood retains it's original and untreated appearance. To be used as a primer.

### RANGE OF APPLICATION

Industrial application for wood flooring and wood panels. Only for interior use.

### PACKAGING

5lt - 25 lt

### SHELF-LIFE

In well-closed and original packaging: minimum 12 months.

### WAREHOUSING

At 10 - 40 °C

### CLEANING

HYDRO CLEANER 7984

### PROTECTION

NATURAL OILS, UV OILS, LACQUERS.

### IMPORTANT INFORMATION

- ECOFIX, ECOFIX WOODLOOK and OCULTO skins fast in contact with air, if necessary filter before use.
- It is recommended to first make a test on the wood before starting the production.
- Be aware of discoloration or delamination because of the substances in the wood or special wood species.
- After use, rinse the material directly with HYDRO CLEANER and water.

### APPLICATION

#### Preparation substrate:

Prepare the wood according the rules of the art and remove the sanding dust carefully.

#### Processing:


- Stir well before use.
- Stain the wood if required with REACTIVE STAINS or waterbased stains.
- Application quantity: 50 - 60 g/m<sup>2</sup>.

### APPLICATION MATERIAL



### TECHNICAL DATA

Extra component:	-
Mixing ratio:	Optional 10% - 20% in water
Pot-life:	-
Density:	2.9 kg/l
Viscosity:	-
Colors:	Off white
Solid content:	100%
Gloss:	-
Thinner:	Water
Coverage per coat:	Depending on the effect to achieve.
Coverage USA per coat:	Depending on the effect to achieve.
Drying:	3 hrs - 4 hrs at room temperature Forced drying possible.



#### Brushing

#### Spray

WOODLOOK  
ECOFIX  
OCULTO

#### Racking

# WOODLOOK ROLL / ECOFIX ROLL / OCULTO ROLL

## PRODUCT DESCRIPTION

ECOFIX ROLL, WOODLOOK ROLL and OCULTO ROLL are water based impregnation oils for parquet and wooden furniture. The wood retains its original and untreated appearance. To be used as a primer.

## RANGE OF APPLICATION

Industrial application for wood flooring and wood panels. Only for interior use.

## PACKAGING

5lt - 20 lt

## SHELF-LIFE

In well-closed and original packaging: minimum 12 months.

## WAREHOUSING

At 10 - 40 °C

## CLEANING

HYDRO CLEANER 7984

## TECHNICAL DATA

Extra component:	-
Mixing ratio:	-
Pot-life:	-
Density:	1.03 kg/l
Viscosity:	ca. 20 sec DIN 8 20 °C
Colors:	Milky
Solid content:	ca. 36%
Gloss:	ca. 15 Gu at 60°
Thinner:	Water
Coverage per coat:	ca. 30 g/m <sup>2</sup>
Coverage USA per coat:	ca. 3 g/ft <sup>2</sup>
Drying:	3 hrs - 4 hrs at room temperature Forced drying possible.

## PROTECTION

NATURAL OILS, UV OILS, LACQUERS.

## IMPORTANT INFORMATION

- ECOFIX ROLL, WOODLOOK ROLL and OCULTO ROLL skins fast in contact with air, if necessary filter before use.
- It is recommended to first make a test on the wood before starting the production.
- Be aware of discoloration or delamination because of the substances in the wood or special wood species.
- Use only stainless material.
- After use, rinse the material directly with HYDRO CLEANER and water.

## APPLICATION

### Preparation substrate:

Prepare the wood according to the rules of the art and remove the sanding dust carefully.

### Processing:

- Stir well before use.
- Stain the wood if required with REACTIVE STAINS or waterbased stains.
- Application quantity: ca. 30 g/m<sup>2</sup>.

## APPLICATION MATERIAL




WOODLOOK



ECOFIX



OCULTO



Brushing

Sponge Roller

WOODLOOK ROLL  
ECOFIX ROLL  
OCULTO ROLL

Hard Roller

Forced Drying  
Hot Air - IR

# Color Fixing Primers

## ENVIRONMENT OIL 5140 BARE TIMBER

### PRODUCT DESCRIPTION

ORIGINAL WOOD ENVIRONMENT OIL 5140 BARE TIMBER is a fast-drying, water-based oil for the impregnation of all floors for indoor use. This oil has been specially developed for the industrial oiling of parquet floors to strengthen their surfaces and protect them from stains and moisture while maintaining a very realistic raw wood look. This oil is only for industrial oiling using a roller coating machine.

### RANGE OF APPLICATION

Industrial application for wood flooring and wood panels. Only for interior use.

### SHELF-LIFE

1 year in closed original packaging. Store away from frost.

### WAREHOUSING

At 10 - 40 °C

### CLEANING

HYDRO CLEANER 7984

### TECHNICAL DATA

Extra component:	AQUA PRO HARDENER
Mixing ratio:	10/1
Pot-life:	1 hour
Density:	1 to 1,1 kg/l
Viscosity:	-
Colors:	-
Solid content:	-
Gloss:	5 Gu at 60°
Thinner:	-
Coverage per coat:	25-40 g/m <sup>2</sup>
Coverage USA per coat:	-
Drying:	1 to 4 hours. Forced drying possible

### PROTECTION

UV OILS, LACQUERS

### IMPORTANT INFORMATION

- It is recommended to first make a test on the wood before starting the production.
- Be aware of discoloration or delamination because of the substances in the wood or special wood species.
- After use, rinse the material directly with HYDRO CLEANER and water.

### APPLICATION

#### Preparation substrate:

Recommended wood preparation: Tynex 46.46 and 80 light brush.

#### Processing:


- ORIGINAL WOOD ENVIRONMENT OIL 5140 BARE TIMBER is applied with a 2 to 3 layer coater with a layer weight of 35 +/- 5 g/m<sup>2</sup> for the first layer and 25 +/- 5 g/m<sup>2</sup> for the subsequent coats. Its high viscosity makes it easy to apply the indicated weights.
- ORIGINAL WOOD ENVIRONMENT OIL 5140 BARE TIMBER is used with 10% AQUA PRO HARDENER.
- Use in a high traffic area: the application of a third layer is necessary.

### DRYING

ORIGINAL WOOD ENVIRONMENT OIL 5140 BARE TIMBER dries in 1 hour at 25 °C between cart layers and 4 hours at 25 °C before packing.

Drying can be accelerated by drying in an oven or hot room.

### APPLICATION MATERIAL



Brushing

Soft Roller  
20 shore

ENVIRONMENT  
OIL 5140

Hard Roller  
40 shore

ENVIRONMENT  
OIL 5140

Forced Drying  
Hot Air - IR

# UV WATER BASE OIL 5133 ROUGH TIMBER

## PRODUCT DESCRIPTION

UV WATER BASE OIL ROUGH TIMBER 5133 penetrates into the core of solid wood for long-lasting protection. It treats and gives a real raw wood natural finish to wood floors at the same time. Snapshot drying under Ultraviolet lamps and immediate storage. Formaldehyde and solvent free. High chemical resistance.

## RANGE OF APPLICATION

Specially created for an industrial application of oil on wooden floors to reinforce the surface of the wood and protect it to stains and humidity. It can be used alone or under an oil or varnish.

## SHELF-LIFE

1 year in closed original packaging. Store away from frost.

## WAREHOUSING

At 10 - 40 °C

## CLEANING

HYDRO CLEANER 7984

## TECHNICAL DATA

Extra component:	-
Mixing ratio:	-
Pot-life:	-
Density:	1 to 1,1 kg/l
Viscosity:	-
Colors:	-
Solid content:	-
Gloss:	8 à 10 Gu at 60°
Thinner:	-
Coverage per coat:	-
Coverage USA per coat:	-
Drying:	Forced drying.

## PROTECTION

UV OILS, LACQUERS.

## IMPORTANT INFORMATION

- It is recommended to first make a test on the wood before starting the production.
- Be aware of discoloration or delamination because of the substances in the wood or special wood species.
- Use only stainless material.
- After use, rinse the material directly with HYDRO CLEANER and water.

## APPLICATION

### Preparation substrate:

Prepare the wood according the rules of the art and remove the sanding dust carefully.

### Processing:


- UV WATER BASE OIL ROUGH TIMBER 5133 is applicated with a roller-coater 20 shore or with spray guns.
- A double application with a wet-on-wet roller is recommended on brushed wood.
- It is possible to make all the possible variations of raw wood: from beige to white by adjusting the percentage of WHITE CONCENTRATE 2024 into UV WATER BASE OIL ROUGH TIMBER 5133. The second layer of UV SOLID OIL can also be tinted to offer more color combinations.
- In combination with the UV SOLID OIL SNOW 5184 in second layer, we remove the pink shade of the oak.

## DRYING

UV WATER BASE OIL ROUGH TIMBER 5133 dries under an oven, 30 seconds at 50 °C and then 1 lamp of 120 W/cm at 10 m/min.

If the process does not have a UV lamp at the exit of the oven, it is possible to apply an UV SOLID OIL in a second layer, wet-on-wet on UV WATER BASE OIL ROUGH TIMBER 5133 and then, dry all under UV lamps. Infrared tunnel drying is also possible.

## APPLICATION MATERIAL





[www.industry.blanchongroup.com](http://www.industry.blanchongroup.com)

Onledebeekstraat 9 - 8800 Roeselare Beveren | Tel. +32 (0)51 30 11 40 - E-mail: [info@ciranova.be](mailto:info@ciranova.be)



A brand of  **Blanchon**  
Group

50, 8<sup>ème</sup> rue | 69800 Saint-Priest  
Tel. +33 472 89 06 06  
[www.blanchongroup.com](http://www.blanchongroup.com)