



High Quality Woodcare Products
Industrial Finishes



Natural Oils

HARDWAXOIL MAGIC

PRODUCT DESCRIPTION

Flooring oil suitable for oil finishing of wooden floors. Good filling properties, natural colour, good chemical and mechanical resistance. Does not shine and is very matt. The durability can be improved by adding the hardener UA 100:5 (optional).

RANGE OF APPLICATION

Industrial application for wood flooring and wood panels. Only for interior use.

CERTIFICATES/LABELS

CpdH / A+ (Fr) / AgBB / Belgian indoor Pass.

PACKAGING

5L - 25L

SHELF-LIFE

In well-closed and original packaging: minimum 24 months.

WAREHOUSING

At 10 - 40 °C

TECHNICAL DATA

Extra component:	HARDENER UA
Mixing ratio:	100:5
Pot-life:	ca. 6 hrs
Density:	Depends on color.
Viscosity:	ca. 50" DIN 4 (at 20 °C)
Colors:	16 colors available
Solid content:	ca. 47%
Gloss:	Matt - Satin
Thinner:	OIL RETARDER
Coverage per coat:	ca. 20 - 25 g/m ²
Coverage USA per coat:	ca. 2 - 2.5 g:ft ²
Drying:	6 - 12 hrs depending on the color.

PROTECTION

Always end with a CLEAR OIL on top.

MAINTENANCE

- Please consult the maintenance program from Ciranova®.

IMPORTANT INFORMATION.

- Used cloths or pads should be plunged in water because of the danger of spontaneous combustion.
- We recommend HARDWAXOIL MAGIC NATURAL as topcoat on the pigmented HARDWAXOILS.
- Colored HARDWAXOILS should always be tested before treating the entire surface.
- Used sanding grain, type of wood,... may affect the final color.

CLEANING

COMBI CLEANER 2879

APPLICATION



Preparation substrate:

Prepare the wood according the rules of the art and remove the sanding dust carefully.

Processing:

- Mix the oil with the hardener (100:5) and let the product rest for about 10 minutes.
- When needed color the wood with stains from Ciranova® INDUSTRIAL FINISHES.
- Can be applied with a roller coater and can be buffed after with a white or beige pad.
- Use brushes to remove the marks of the buffing pads.

APPLICATION MATERIAL



HARDWAXOIL HIGH SOLID

PRODUCT DESCRIPTION

HARDWAXOIL HIGH SOLID 5167 NATURAL is based on HARDWAXOIL penetrating into the core of solid wood for long-lasting protection. It treats and gives a natural finish to wood floors at the same time. A wide possibility of colours is achieved through the use of pigment pastes. Addition of pigment pastes for colour creation: WHITE 3000, RED 3001, YELLOW 3002, BLACK 3003 and BRIGHT RED 3004.

RANGE OF APPLICATION

HARDWAXOIL HIGH SOLID 5167 NATURAL is specially created for an industrial application of oil on wooden floors for reinforce the surface of the wood and protect it to stains and humidity.

SHELF-LIFE

1 year in closed original packaging. Store away from frost.

WAREHOUSING

At 10 - 40 °C

TECHNICAL DATA

Extra component:	-
Mixing ratio:	-
Pot-life:	-
Density:	0,89 kg/l
Viscosity:	-
Colors:	-
Solid content:	-
Gloss:	-
Thinner:	-
Coverage per coat:	30-35 g/m ² per coat
Coverage USA per coat:	-
Drying:	8 hours.

IMPORTANT INFORMATION

Clean rags and tools immediately after use or store in water. Do not throw rags or tools soaked in oil without rinsing them with water.

MIXING PASTE

Used for mixing in clear HARDWAXOIL HIGH SOLID in order to create your own colors. Thanks to the mixing pastes you don't need a stock of plenty colours and you can create fast and easy your colors.

APPLICATION


Preparation substrate:

Prepare the wood according the rules of the art and remove the sanding dust carefully.

Processing:

- HARDWAXOIL HIGH SOLID 5167 NATURAL is applied in 2 coats with the roller or spray machine 30-35 g/m² per coat. Surface level brushing and surface light sanding contribute to a smooth and aesthetically pleasing oiled surface.
- Available in matte version under codes 5144 (more matt than 5167) and 5145 (matt between 5167 and 5144). Possibility of application in 2nd layer on 5167 without wiping to adjust an intermediate gloss.

APPLICATION MATERIAL



Natural Oils

HARDWAXOIL TITAN

PRODUCT DESCRIPTION

HARDWAXOIL TITAN is a special oil suitable for oil finishing of wooden floors. Good filling properties, very natural color, good chemical and mechanical resistance. The HARDWAXOIL TITAN has a long open time which makes it very appropriate to apply by roller and rollercoater.

RANGE OF APPLICATION

Industrial application for wood flooring and wood panels. Only for interior use.

CERTIFICATES/LABELS

Indoor Air comfort.

PACKAGING

5L - 25L

SHELF-LIFE

In well-closed and original packaging: minimum 24 months.

WAREHOUSING

At 10 - 40 °C

TECHNICAL DATA

Extra component:	HARDENER UA
Mixing ratio:	100:5
Pot-life:	ca. 6 hours.
Density:	Depends on color.
Viscosity:	ca. 50 sec DIN 4 (at 20 °C)
Colors:	Clear
Solid content:	ca. 46%
Gloss:	Matt - Silk - Satin
Thinner:	Oil Retarder
Coverage per coat:	ca. 20 - 25 g/m ²
Coverage USA per coat:	ca. 2 - 2.5 g:ft ²
Drying:	Can be overcoated after +/- 6 - 12 hours. The drying time is very dependent on the applied quantity, the temperature and air ventilation in the room.

PROTECTION

HARDWAXOIL TITAN can be used as base and topcoat.

MAINTENANCE

Please consult the maintenance program from Ciranova®.

IMPORTANT INFORMATION

- Used cloths or pads should be plunged in water because of the danger of spontaneous combustion.
- We recommend HARDWAXOIL TITAN as topcoat on the pigmented HARDWAXOILS.
- Colored HARDWAXOILS should always be tested before treating the entire surface.
- Used sanding grain, type of wood,... may affect the final color.

CLEANING

COMBI CLEANER 2879

APPLICATION


Preparation substrate:

Prepare the wood according the rules of the art and remove the sanding dust carefully.

Processing:

- Mix the oil with the HARDENER (100:5) and let the product rest for about 10 minutes.
- When needed color the wood with stains from Ciranova® INDUSTRIAL FINISHES. Can be applied with a roller coater.
- Use brushes to remove marks.
- After drying, a second or even a third coat is recommended.

APPLICATION MATERIAL



UN1CO

PRODUCT DESCRIPTION

UN1CO is a 2 component, 1-coat oil from the newest generation using renewable natural raw materials. Thanks to its special technology there is only one coat needed to finish your parquet. The combination of the oil with the hardener results in a fast drying and excellent chemical and mechanical resistant finish. UN1CO is VOC and Cobalt free.

RANGE OF APPLICATION

Industrial application for wood flooring and wood panels. Only for interior use.

CERTIFICATES/LABELS

Indoor Air confort GOLD / EN13501 B fl s1.

PACKAGING

1lt - 20lt

SHELF-LIFE

In well-closed and original packaging: minimum 12 months.

WAREHOUSING

At 10 - 40 °C

TECHNICAL DATA

Extra component:	HARDENER UN1CO
Mixing ratio:	100:30
Pot-life:	ca. 3 hours.
Density:	Depends on color.
Viscosity:	ca. 40 sec DIN 4 (at 20 °C)
Colors:	16 colors available
Solid content:	ca. 100%
Gloss:	Matt - depending on the applied quantity.
Thinner:	-
Coverage per coat:	ca. 15 - 20 g/m ²
Coverage USA per coat:	ca. 1.5 - 2 g/ft ²
Drying:	ca. 24 hours at room temperature. Depending on air circulation and temperatures.

PROTECTION

UN1CO colors and protects in only 1 coat.

MAINTENANCE

Please consult the maintenance program from Ciranova®.

IMPORTANT INFORMATION

- Used cloths or pads should be plunged in water because of the danger of spontaneous combustion.
- Colored HARDWAXOILS should always be tested before treating the entire surface.
- Used sanding grain, type of wood,... may affect the final color.

CLEANING

COMBI CLEANER 2879

APPLICATION



Preparation substrate:

Prepare the wood according the rules of the art and remove the sanding dust carefully.

Processing:

- Mix the oil with the HARDENER (100/30) and let the product rest for about 10 minutes.
- When needed color the wood with stains from Ciranova® INDUSTRIAL FINISHES.
- UN1CO can be applied with a roller coater and can be buffed after with a white or beige pad.
- Use brushes to remove the marks of the buffing pads.

APPLICATION MATERIAL





www.industry.blanchongroup.com

Onledebeekstraat 9 - 8800 Roeselare Beveren | Tel. +32 (0)51 30 11 40 - E-mail: info@ciranova.be



A brand of  **Blanchon**
Group

50, 8^{ème} rue | 69800 Saint-Priest
Tel. +33 472 89 06 06
www.blanchongroup.com